

MOISTURE-CURABLE ADHESIVE COMPOSITION

Publication number: JP7126600

Publication date: 1995-05-16

Inventor: KUDO KAZUSUKE; ZENKI YASUKAZU

Applicant: SEKISUI CHEMICAL CO LTD

Classification:

- international: C08G18/42; C09J175/00; C09J175/04; C08G18/42;
C08G18/00; C09J175/00; C09J175/04; C08G18/00;
(IPC1-7): C08G18/42; C09J175/04

- European:

Application number: JP19930271759 19931029

Priority number(s): JP19930271759 19931029

Report a data error here

Abstract of JP7126600

PURPOSE: To obtain a moisture-curable adhesive compsn. with a very high curing speed and an excellent initial cohesive force by using a specified crystalline polyester polyol as a constituent of a urethane prepolymer prepolymer having isocyanate groups on its molecular terminals.

CONSTITUTION: In the adhesive compsn., a urethane prepolymer is formed by using a mixture of a polyester polyol A which is crystalline at ordinary temp. and a polyester polyol with a rosin skeleton in its molecule or a polyester polyol with a rosin skeleton in its molecule B, or a polyester polyol C which is crystalline at ordinary temp. and having a rosin skeleton in its molecule. The polyols A and C are prepd. by reacting a glycol having a molecular chain structure of $-(CH_2)_n$ with a dicarboxylic acid having a molecular chain structure of $-(CH_2)_m$ and at least one of polyester polyols satisfying the conditions of $14 \leq n+m$ or $8 \leq n+m \leq 14$.

Data supplied from the *esp@cenet* database - Worldwide